

5000HD Air drill specifications

Base Size	39 ft (11.9 m)	45 ft (13.7 m)	51 ft (15.6 m)	57 ft (17.4 m)
# Sections	3	5	5	5

Dimensions – Transport

Length	29 ft (8.8 m)	29 ft (8.8 m)	29 ft (8.8 m)	29 ft (8.8 m)
Height	17 ft 6 in (5.3 m)	13 ft 6 in (4.1 m)	17 ft 6 in (5.3 m)	16 ft 11 in (5.2 m)
Width	20 ft 6 in (6.2 m)	20 ft 6 in (6.2 m)	20 ft 6 in (6.2 m)	20 ft 6 in (6.2 m)

Spacing Options

9.875 in (25.0 cm)

Number of shanks	48	56	62	70
Working Width ft (m)	39.5 ft (12 m)	46.1 ft (14.1 m)	51 ft (15.6 m)	57.6 ft (17.6 m)

12 in (30.5 cm)

Number of shanks	40	46	52	58
Working Width ft (m)	40 ft (12.2 m)	46 ft (14 m)	52 ft (15.9 m)	58 ft (17.7 m)

Tyres

Dual Front Castors (Centre Section)	11 L x 15 (D)	11 L x 15 (D)	11 L x 15 (D)	11 L x 15 (D)
Rear (Centre Section)	11 L x 15 (D)	11 L x 15 (D)	11 L x 15 (D)	11 L x 15 (D)
Dual Front Castors (Wing Section)	9.5 L x 15 (D)	9.5 L x 15 (D)	9.5 L x 15 (D)	9.5 L x 15 (D)

Depth Control

Flexible frame with single point depth setting

Press Wheels Options

Rubber	3 in x 22 in (7.6 cm x 55.9 cm)	Steel	3.5 in x 22 in (8.9 cm x 55.9 cm)
	4 in x 22 in (10.2 cm x 55.9 cm)		4.5 in x 22 in (11.4 cm x 55.9 cm)
	5.5 in x 22 in (14 cm x 55.9 cm)		